



Description

A polyurethane-based sealer designed to be applied to bare or stained interior timber surfaces prior to finishing. Provides an easily sanded film to fill grain prior to application of Clearproof Interior polyurethanes.

Uses

Bare or stained interior timber surfaces such as doors, mouldings and architraves.

Technical

Colour Range

Clear only

Drying And Recoating

Dries in two to four hours. May be overcoated in 16 hours.

Gloss Level

Flat (0-1%)

Odour

Ensure adequate ventilation during use.

Sandability

Excellent

Surface Preparation

Timber should be free of dust, dirt, oil or wax. Punch in any nail heads protruding from surface. Fill holes and cracks with a suitable filler of similar colour to the timber. Sand and dust thoroughly before applying Tradex or ClearProof Interior polyurethane finishes. Thoroughly sand existing polyurethane clears or stains to ensure intercoat adhesion. Take care not to rub through to timber or a patchy finish may result.

Application

Application

Apply one or two coats as required by brush. Sand lightly with fine paper to denib between coats.

Cleanup

Mineral turps

Coverage

Up to 16m²/litre. Coverage on rough or absorbent surfaces will be lower.

Recoat

Recoat after appropriate preparation with polyurethane clear after 16 hours at 25°C and 50% relative humidity.

Stirring

Stir paint with a 25mm wide flat stirrer in a circular lifting motion for at least 5 minutes before use.